

Translated English of Chinese Standard: GB31830-2024

www.ChineseStandard.net → Buy True-PDF → Auto-delivery.

Sales@ChineseStandard.net

GB

NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA

ICS 27.010

CCS F 01

GB 31830-2024

Replacing GB 31828-2015, GB 31830-2015

**Norm of Energy Consumption Per Unit Production of
Toluene Diisocyanate and Diphenyl Methane Diisocyanate**
甲苯二异氰酸酯和二苯基甲烷二异氰酸酯单位产品能源消耗限额

Issued on: April 29, 2024

Implemented on: May 1, 2025

Issued by: State Administration for Market Regulation;

Standardization Administration of the People's Republic of China.

Table of Contents

Foreword	3
1 Scope	4
2 Normative References	4
3 Terms and Definitions	4
4 Norm Level of Energy Consumption	5
5 Technical Requirements	5
6 Statistical Range and Calculation Method	5
Appendix A (Informative) Reference Coefficients of Various Energy Sources Converted to Standard Coal (Reference Values)	9
Appendix B (Informative) Equivalent Energy Values of Various Energy-Consumed Mediums	11

Norm of Energy Consumption Per Unit Production of Toluene Diisocyanate and Diphenyl Methane Diisocyanate

1 Scope

This Document specifies the norm levels, technical requirements, and statistical range of energy consumption per unit production (abbreviated as energy consumption) of toluene diisocyanate (TDI) and diphenyl methane diisocyanate (MDI); and describes the calculation method for them.

This Document is applicable to the calculation and assessment of energy consumption per unit production of TDI produced with dinitrotoluene (DNT), hydrogen, chlorine, and carbon monoxide as raw materials, and MDI produced with aniline, formaldehyde, chlorine, and carbon monoxide as raw materials, as well as energy consumption control for new construction and renovation and expansion projects.

2 Normative References

The provisions in following documents become the essential provisions of this Document through reference in this Document. For the dated documents, only the versions with the dates indicated are applicable to this Document; for the undated documents, only the latest version (including all the amendments) is applicable to this Document.

GB/T 2589 General principles for calculation of total production energy consumption

GB/T 12723 General principles of stipulation of energy consumption norm for unit product

GB/T 13941 Diphenylmethane diisocyanate

GB/T 32469 Plastics - Polyurethane raw materials - Toluene diisocyanate

3 Terms and Definitions

For the purposes of this Document, the terms and definitions given in GB/T 12723 and the following apply.

3.1 Comprehensive energy consumption of toluene diisocyanate product

During the reporting period, the total amount of various energy actually consumed in the entire production process of TDI product.

6.1.1 The comprehensive energy consumption of TDI and MDI products includes various primary energy (raw coal, oil, natural gas, etc.), secondary energy (electricity, heat, petroleum products, coke, gas, etc.) consumed by the production system, auxiliary production system and affiliated production system; and energy-consumed mediums used in production (energy consumed by water, oxygen, compressed air, etc.); excluding energy used in the construction and renovation process and living energy (referring to the energy used in dormitories, schools, cultural entertainment, medical care, commercial services and childcare and early childhood education within the enterprise system).

6.1.2 Energy consumption of TDI and MDI production systems are as follows:

- a) Energy consumption of TDI production system includes: Various energy consumption, using DNT, hydrogen, chlorine, carbon monoxide as raw materials, through hydrogenation unit, phosgene synthesis unit, phosgenation unit, distillation unit to TDI product entering finished product tank and sending out by-product hydrogen chloride gas.
- b) Energy consumption of MDI production system includes: Various energy consumption, using aniline, formaldehyde, chlorine, carbon monoxide as raw materials, through condensation unit, phosgene synthesis unit, phosgenation unit, separation unit to finished MDI tank area and waste liquid, waste residue, waste gas are sent out after pretreatment.

6.1.3 Energy consumption of auxiliary production system includes: Energy consumption of power supply, machine repair, water supply, gas supply, heating, refrigeration, instrument repair, lighting, warehouse and raw material site in the factory, as well as for safety, environmental protection (waste liquid, waste residue, waste gas are sent out after pretreatment), energy saving and other devices that facilities serving the production system.

6.1.4 Energy consumption of auxiliary production system includes: Energy consumption of dispatch room, office, operation room, control room, lounge, dressing room, bathhouse, central control analysis, product inspection, maintenance section and other facilities specially configured for the production system.

6.1.5 The waste heat, waste energy and chemical reaction heat generated in the recycling and utilization production process of TDI and MDI are not included in the energy consumption. If the waste heat, waste energy and chemical reaction heat are used by other devices outside the statistical range of 6.1.2 ~ 6.1.4, they shall be deducted from the system according to the actually used energy.

6.1.6 The statistics and accounting of energy consumption shall include all production links and systems; and shall neither be repeated nor omitted. The energy consumed by routine overhaul and storage loss shall be included in the energy consumption of the production system.

6.2 Calculation method

6.2.1 The calculation of comprehensive energy consumption shall comply with the provisions of GB/T 2589.

6.2.2 The calorific value of various energy sources shall be converted into a unified unit of measurement, kilograms of standard coal (kgce). The calorific value of various energy sources shall be based on the actual measured value of the enterprise during the reporting period. If there is no actual measurement condition, the reference coefficients of various energy sources for standard coal conversion given in Appendixes A or B may be used for conversion.

6.2.3 The outsourced steam shall be converted into standard coal according to the enthalpy value of the purchased steam.

6.2.4 The output of TDI and MDI products shall be the physical quantity of qualified products. TDI products shall meet the quality requirements of GB/T 32469; and qualified MDI products shall meet the quality requirements of GB/T 13941.

6.2.5 The comprehensive energy consumption of TDI and MDI products shall be calculated according to Formula (1).

$$E = \sum_{i=1}^m (e_{is} \times K_i) + \sum_{j=1}^n (e_{jf} \times K_j) - \sum_{r=1}^l (e_{rh} \times K_r) \quad \dots\dots\dots (1)$$

Where:

E - Comprehensive energy consumption of TDI and MDI products, in kilograms of standard coal (kgce);

m - Number of energy types input into the production system;

e_{is} - Physical quantity of the i^{th} energy input into the production system of TDI and MDI products;

K_i - The standard coal conversion coefficient of the i^{th} energy input into the production system;

n - Number of energy types input into the auxiliary production system and the subsidiary production system;

e_{jf} - Physical quantity of the j^{th} energy input into the auxiliary production system and the subsidiary production system of TDI and MDI products;

K_j - The standard coal conversion coefficient of the j^{th} energy input into the auxiliary production system and the subsidiary production system;

l - Number of energy types recovered in the production process and used by devices outside the statistical range;

e_{rh} - Physical quantity of the r^{th} energy recovered in the production process of TDI and MDI products and used by devices outside the statistical range;

K_r - The standard coal conversion coefficient of the r^{th} energy recovered in the production

This is an excerpt of the PDF (Some pages are marked off intentionally)

Full-copy PDF can be purchased from 1 of 2 websites:

1. <https://www.ChineseStandard.us>

- SEARCH the standard ID, such as GB 4943.1-2022.
- Select your country (currency), for example: USA (USD); Germany (Euro).
- Full-copy of PDF (text-editable, true-PDF) can be downloaded in 9 seconds.
- Tax invoice can be downloaded in 9 seconds.
- Receiving emails in 9 seconds (with download links).

2. <https://www.ChineseStandard.net>

- SEARCH the standard ID, such as GB 4943.1-2022.
- Add to cart. Only accept USD (other currencies - <https://www.ChineseStandard.us>).
- Full-copy of PDF (text-editable, true-PDF) can be downloaded in 9 seconds.
- Receiving emails in 9 seconds (with PDFs attached, invoice and download links).

Translated by: Field Test Asia Pte. Ltd. (Incorporated & taxed in Singapore. Tax ID: 201302277C)

About Us (Goodwill, Policies, Fair Trading...): <https://www.chinesestandard.net/AboutUs.aspx>

Contact: Wayne Zheng, Sales@ChineseStandard.net

Linkin: <https://www.linkedin.com/in/waynezhengwenrui/>

----- The End -----