

Translated English of Chinese Standard: GB/T1003-2016
www.ChineseStandard.net → Buy True-PDF → Auto-delivery.
Sales@ChineseStandard.net

GB

NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA

ICS 29.120.30

K 30

GB/T 1003-2016

Replacing GB 1003-2008

**Three phases plugs and socket-outlets for household
and similar purposes - Types, basic parameters and
dimensions**

家用和类似用途三相插头插座 型式、基本参数和尺寸

Issued on: December 13, 2016

Implemented on: July 01, 2017

**Issued by: General Administration of Quality Supervision, Inspection and
Quarantine;**

**Standardization Administration of the People's Republic of
China.**

Table of Contents

Foreword.....	3
1 Scope.....	5
2 Normative references.....	5
3 Terms and definitions	5
4 Technical requirements and test methods.....	5
5 Types, basic parameters and dimensions	6

Foreword

This Standard was drafted in accordance with the rules given in GB/T 1.1-2009.

This Standard replaces GB 1003-2008 "Three phases plugs and socket-outlets for household and similar purposes - Types, basic parameters and dimensions".

Compared with GB 1003-2008, the main technical changes in GB 1003-2008 are as follows:

- added the use method for special gauges in 5.1;
- added the description of the position of the ground electrode and the neutral electrode in 5.2;
- modified "The distance between the plug pin and the edge shall ensure that it meets the requirements for protection against electric shock" to "The distance between the plug pin of the live plug and the edge shall not be less than 7.5mm" in 5.3;
- added the minimum distance between insert sleeve and mating surface in 5.4;
- added the shapes and dimensions of the end of the pin for the plugs in Figure 1, Figure 3;
- added Figure 3 Three-phase five-wire plug and its dimensions;
- added Figure 4 Three-phase five-wire socket and its dimensions;
- deleted original Figure 3 Three-phase plug inner gauge and original Figure 4 Three-phase plug external gauge; combined them as Figure 5 Three-phase five-wire plug gauge;
- deleted original Figure 5 Maximum go gauge of three-phase socket and original Figure 6 Minimum go gauge of three-phase socket; combined them as Figure 6 Three-phase five-wire socket go gauge;
- modified original Figure 7 Three-phase socket not-go gauge to Figure 7 Three-phase five-wire socket not-go gauge;
- added Figure 8 Three-phase five-wire socket non-contact gauge and its dimensions;
- added Figure 9 Three-phase socket live socket contact gauge;
- added Figure 10 Schematic diagram of the arrangement facing the three-phase five-wire socket.

Three phases plugs and socket-outlets for household and similar purposes - Types, basic parameters and dimensions

1 Scope

This Standard specifies the types, basic parameters and dimensions of three phases plugs and socket-outlets for household and similar purposes.

This Standard is applicable to three-phase plugs and three-phase fixed or mobile sockets for household and similar purposes, of which the AC frequency is 50Hz, the rated voltage is 440V, the rated current does not exceed 32A.

This Standard does not exclude the use of three-phase plugs and sockets for construction sites, or for agricultural and commercial purposes.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

GB/T 1184, *Geometrical tolerancing - Geometrical tolerance for features without individual tolerance indications* (GB/T 1184-1996, eqv ISO 2768-2:1989)

GB 2099.1-2008, *Plugs and socket-outlets for household and similar purposes - Part 1: General requirements* (IEC 60884-1:2006, Ed 3.1, MOD)

3 Terms and definitions

For the purposes of this document, the terms and definitions defined in GB 2099.1-2008 apply.

4 Technical requirements and test methods

The technical requirements and test methods of three-phase plugs and sockets for household and similar purposes shall meet the requirements of GB 2099.1-

2008.

5 Types, basic parameters and dimensions

5.1 The types, basic parameters and dimensions of three-phase plugs and sockets for household and similar purposes shall meet the requirements in Figure 1 to Figure 4.

To inspect these dimensions, use the special gauges specified in Figure 5, Figure 6, Figure 7, Figure 8, and Figure 9 and a vernier caliper with a graduation of 0.02mm. The insertion force of the gauge shall not be greater than the maximum extraction force specified in GB 2099.1-2008. The roughness of these gauges are all $\sqrt{0.8}$. The hardness is HRC58~HRC62. The geometric tolerances of the parallelism, perpendicularity and symmetry of the gauge are in accordance with the tolerance level H specified in GB/T 1184.

The use methods of special gauges are as follows:

- The three-phase plug shall be able to insert the gauge shown in Figure 5;
- The universal gauge shown in Figure 6 shall be able to be inserted into the socket of the three-phase five-wire socket panel. For three-phase four-wire sockets, use a go gauge that removes the neutral pole of Figure 6;
- The not-go gauge shown in Figure 7 shall not be inserted into the socket of the three-phase five-wire socket panel. For three-phase four-wire sockets, use the not-go gauge that removes the neutral pole of Figure 7;
- The non-contact gauge shown in Figure 8 shall not touch the live socket of the socket. For three-phase four-wire sockets, use a non-contact gauge that removes the neutral pole of Figure 8;
- The contact gauge shown in Figure 9 shall be able to touch the live socket of the corresponding three-phase socket.

5.2 The positions of the grounding pole and neutral pole of the three-phase socket are arranged as follows: Face the socket. The ground electrode is in the upper position. The neutral pole is in the middle. The arrangement is shown in Figure 10. In addition, the location of the jack shall be clearly marked.

5.3 The shape of the plug is not specified. However, the distance between the plug pin of the live plug and the edge shall not be less than 7.5mm.

5.4 Except for the grounding socket, the distance between the live socket in the three-phase socket and the mating surface shall not be less than the distance specified in Table 1.

This is an excerpt of the PDF (Some pages are marked off intentionally)

Full-copy PDF can be purchased from 1 of 2 websites:

1. <https://www.ChineseStandard.us>

- SEARCH the standard ID, such as GB 4943.1-2022.
- Select your country (currency), for example: USA (USD); Germany (Euro).
- Full-copy of PDF (text-editable, true-PDF) can be downloaded in 9 seconds.
- Tax invoice can be downloaded in 9 seconds.
- Receiving emails in 9 seconds (with download links).

2. <https://www.ChineseStandard.net>

- SEARCH the standard ID, such as GB 4943.1-2022.
- Add to cart. Only accept USD (other currencies - <https://www.ChineseStandard.us>).
- Full-copy of PDF (text-editable, true-PDF) can be downloaded in 9 seconds.
- Receiving emails in 9 seconds (with PDFs attached, invoice and download links).

Translated by: Field Test Asia Pte. Ltd. (Incorporated & taxed in Singapore. Tax ID: 201302277C)

About Us (Goodwill, Policies, Fair Trading...): <https://www.chinesestandard.net/AboutUs.aspx>

Contact: Wayne Zheng, Sales@ChineseStandard.net

Linkin: <https://www.linkedin.com/in/waynezhengwenrui/>

----- The End -----