

Translated English of Chinese Standard: GB/T36229-2018
www.ChineseStandard.net → Buy True-PDF → Auto-delivery.
Sales@ChineseStandard.net

GB

NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA

ICS 25.120.01

J 62

GB/T 36229-2018

**Reliability assessment method and index of active
optoelectronic protective device**

光电保护装置可靠性考核方法和指标

Issued on: May 14, 2018

Implemented on: December 01, 2018

Issued by: State Administration for Market Regulation;

**Standardization Administration of the People's Republic of
China.**

Table of Contents

Foreword.....	3
1 Scope.....	4
2 Normative references.....	4
3 Terms and definitions	4
4 Assessment conditions	5
5 Assessment method.....	5
6 Test methods.....	7
7 Assessment index	10
8 Determination of assessment results	11
9 Assessment record	11
Annex A (informative) Assessment record of reliability of active optoelectronic protective device	12

Reliability assessment method and index of active optoelectronic protective device

1 Scope

This Standard specifies assessment conditions, assessment methods, test methods, assessment indicators, assessment results and assessment records for reliability of active optoelectronic protective device.

This Standard is applicable to reliability assessment of active optoelectronic protective device.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

GB/T 2900.13, *Electrotechnical terminology - Dependability and quality of service*

GB/T 4584, *Specification of active opto-electronic protective devices for presses*

GB/T 17626.2-2006, *Electromagnetic compatibility (EMC) - Testing and measurement techniques - Electrostatic discharge immunity test*

GB/T 17626.4-2008, *Electromagnetic compatibility - Testing and measurement techniques - Electrical fast transient/burst immunity test*

GB/T 17626.5-2008, *Electromagnetic compatibility - Testing and measurement techniques - Surge immunity test*

3 Terms and definitions

For the purposes of this document, the terms and definitions specified in GB/T 2900.13, GB/T 4584 apply.

5.5.3 Detection after test

After the test, the sample shall be subjected to the sensing function, response time and anti-electromagnetic interference detection test according to the requirements of Clause 6. If the test result does not meet the requirements after the test, it is considered that the sample is invalid. The expiration time is based on the number of times at the end of the test.

6 Test methods

6.1 Induction function

6.1.1 Light-passing function

Under the conditions of use specified by the sample, the active optoelectronic protective device shall have a light-passing function, that is, when there is no shade in the light curtain area, the light curtain shall continue to pass light, and the active optoelectronic protective device outputs an "on" switch state signal. The active optoelectronic protective device shall have an induction function under the conditions of use specified in the sample. When the light-shielding rod (test piece) enters the light curtain area, the active optoelectronic protective device shall respond within the response time and output an "off" switch status signal. When the light-shielding rod (test piece) is removed from the light curtain area, the light curtain shall be re-transmitted, and the active optoelectronic protective device output switch status signal shall change from "off" to "on".

6.1.2 Light-passing test (A test)

The light curtain of the active optoelectronic protective device is illuminated within the rated protection length without interference or other specified events in the detection zone. Observe the output status signal of the active optoelectronic protective device for at least 5s. Unless otherwise specified, OSSD(s) shall be on during this period and shall not be disconnected.

6.1.3 Induction function test (B test)

6.1.3.1 The light curtain of the active optoelectronic protective device is illuminated within the rated protection length without interference or other specified events in the detection zone. Observe the output status signal of the active optoelectronic protective device for at least 5s. Unless otherwise specified, OSSD(s) shall be on during this period and shall not be disconnected.

6.1.3.2 Put the test piece into the detection area or start the specified event. During the response time, the output status signal of the active optoelectronic protective device shall be switched from the on state to the off state. Observe the output status signal for at least 5s. Unless otherwise specified, the output

optoelectronic protective device is not less than 106 times.

8 Determination of assessment results

8.1 The average number of trouble-free operations (life) per sample is the number of trials at the time of failure.

8.2 The average number of trouble-free operations (life) of the active optoelectronic protective device is based on the average of all test samples.

8.3 There is no sample failure during the reliability assessment, and the service life is the set test time (number of times).

9 Assessment record

9.1 An assessment record shall be established for each sample. And perform test data recording in sequential order. The content of the record shall be:

- a) Sample name, model, specification;
- b) Manufacturer and date of manufacture;
- c) Test date and number of samples;
- d) Test conditions;
- e) Failure sample number and related test times;
- f) Failure phenomenon;
- g) Failure analysis and judgment;
- h) Tester.

9.2 See Annex A for the recommended assessment report format.

This is an excerpt of the PDF (Some pages are marked off intentionally)

Full-copy PDF can be purchased from 1 of 2 websites:

1. <https://www.ChineseStandard.us>

- SEARCH the standard ID, such as GB 4943.1-2022.
- Select your country (currency), for example: USA (USD); Germany (Euro).
- Full-copy of PDF (text-editable, true-PDF) can be downloaded in 9 seconds.
- Tax invoice can be downloaded in 9 seconds.
- Receiving emails in 9 seconds (with download links).

2. <https://www.ChineseStandard.net>

- SEARCH the standard ID, such as GB 4943.1-2022.
- Add to cart. Only accept USD (other currencies - <https://www.ChineseStandard.us>).
- Full-copy of PDF (text-editable, true-PDF) can be downloaded in 9 seconds.
- Receiving emails in 9 seconds (with PDFs attached, invoice and download links).

Translated by: Field Test Asia Pte. Ltd. (Incorporated & taxed in Singapore. Tax ID: 201302277C)

About Us (Goodwill, Policies, Fair Trading...): <https://www.chinesestandard.net/AboutUs.aspx>

Contact: Wayne Zheng, Sales@ChineseStandard.net

Linkin: <https://www.linkedin.com/in/waynezhengwenrui/>

----- The End -----