

Translated English of Chinese Standard: GB/T40337-2021
www.ChineseStandard.net → Buy True-PDF → Auto-delivery.
Sales@ChineseStandard.net

GB

NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA

ICS 25.160.30

CCS J 64

GB/T 40337-2021

**Gas Tightness of Equipment for Gas Welding and
Allied Processes**

(ISO 9090:2019, MOD)

气焊及相关工艺设备的气密性

Issued on: May 21, 2021

Implemented on: December 01, 2021

**Issued by: State Administration for Market Regulation;
Standardization Administration of PRC.**

Table of Contents

Foreword.....	4
1 Scope.....	5
2 Normative References	5
3 Terms and Definitions	5
4 Expression of Leakage	6
5 Test Gas.....	6
5.1 General principles	6
5.2 Type test.....	6
5.3 Routine test	6
6 Test Pressure	7
6.1 Pressure reducer.....	7
6.2 Other equipment	7
7 The Maximum Allowable Total External Leakage Rate Under the above- Defined Pressure Conditions	7
7.1 Pressure reducer.....	7
7.2 Welding and cutting torch.....	7
7.3 Safety device.....	8
7.4 Quick coupling.....	8
7.5 Devices with combined functions	8
7.6 Hose assembly.....	8
7.7 Other equipment	8
8 Measurement of Leakage Rate.....	8
8.1 General principles	8
8.2 Test principle	8
8.3 Immersion test device	9
8.4 Test procedures.....	9
Appendix A (Informative) Change in Structure between this Document and ISO 9090:2019	11

Appendix B (Informative) Technical Differences and Causes between this Document and ISO 9090:2019	12
Appendix C (Normative) Correction Coefficient	13
Appendix D (Normative) Test Methods for Leakage Rate Measurement of Welding and Cutting Torch	14

Gas Tightness of Equipment for Gas Welding and Allied Processes

1 Scope

This Document specifies the maximum allowable external leakage rate and measurement test methods for welding, cutting and allied process equipment (hereinafter referred to as "equipment").

This Document is applicable to independent welding and cutting equipment parts or devices from the hose connection (the outlet of the gas cylinder valve or the connection end of the gas supply station) at the gas supply end to the gas outlet of the welding and cutting torch.

This Document is not applicable to gas supply stations.

Some equipment standards stipulate the maximum allowable external leakage rate, which shall be implemented in accordance with their standard provisions.

2 Normative References

The following documents are essential to the application of this document. For the dated documents, only the versions with the dates indicated are applicable to this document; for the undated documents, only the latest version (including all the amendments) is applicable to this document.

GB/T 3375 Welding Terminology

GB/T 7899 Regulators for Welding, Cutting and the Similar Processes (GB/T 7899-2006, ISO 2503-1998, MOD)

3 Terms and Definitions

For the purposes of this Document, the terms and definitions given in GB/T 3375 and the following apply.

3.1 External gas leakage

The phenomenon of undesirable gas escaping from the inside of the equipment into the atmosphere.

6 Test Pressure

6.1 Pressure reducer

The pressure reducer of the gas supply system of the welding and cutting equipment shall be tested under the pressure p_1 and p_2 specified in GB/T 7899.

6.2 Other equipment

6.2.1 Type test

Other equipment shall be tested under the following pressures:

- a) The maximum working pressure given by the manufacturer;
- b) 10% of the maximum working pressure or 0.05MPa, whichever is lower.

6.2.2 Routine test

All equipment shall be tested under one of the pressure conditions given in 6.2.1; the pressure conditions shall be the most unfavourable pressure conditions obtained in the type test.

7 The Maximum Allowable Total External Leakage Rate Under the above-Defined Pressure Conditions

7.1 Pressure reducer

The overall leakage rate of the pressure reducer shall be no greater than 10cm³/h.

7.2 Welding and cutting torch

The total external leakage rate of the welding and cutting torch shall be no greater than 8cm³/h. The leakage rate through a separate gas valve shall be no greater than 4cm³/h. The test method is carried out in accordance with the provisions of Appendix D.

The test method given in Appendix D can measure the overall leakage rate of the welding and cutting torch and the leakage rate of a separate gas valve. In the 6 sets of test conditions (Figures D.1 ~ D.6: Blocking the inlet and/or outlet, adjusting the valve switch state, connecting the gas hose to different inlets) for measuring the leakage rate, there are 3 sets of measuring welding/heating torches, and 3 sets of measuring cutting torches. It is stipulated that the leakage rate of the equipment in Figures D.1, D.2, and D.4 shall be no greater than 8cm³/h; and the leakage rate of the equipment in Figures D.3, D.5, and D.6 shall be no greater than 4cm³/h.

Other test methods are allowed, provided that the accuracy of the results obtained by these methods can be proved to be the same as the above methods.

8.3 Immersion test device

8.3.1 The water tank shall be of sufficient size to be able to completely immerse the equipment to be tested in the water.

8.3.2 During the test, allow the air supply end to pressurize the equipment to be tested.

8.3.3 The measuring cylinder shall be filled with water at the beginning of the test and installed above the equipment to be tested. The measuring cylinder range shall be sufficient, and the accuracy shall be no less than 0.5cm³.

8.3.4 The funnel is used to collect the gas escaping from the equipment. The funnel shall be suitable for collecting all gases that may escape from the equipment to be tested. The gas leaking at the connection of the gas supply pipeline shall not be collected.

8.3.5 The immersion test device for measuring the gas leakage rate of the equipment is shown in Figure 1.

8.4 Test procedures

8.4.1 Connect the equipment to be tested with the gas source (see Figure 1, which shall meet the requirements of 8.3.2), close all other possible openings in order to determine the leakage rate.

8.4.2 Immerse the equipment to be tested in water (see Figure 1, which shall meet the requirements of 8.3.1), and the depth shall be at least 20cm. And supply gas to the equipment to be tested according to the test pressure given in Clause 6 plus the pressure Δp generated by the immersion depth.

8.4.3 Wait for 10min; allow the trapped gas adhering to the outer surface of the equipment to be tested to escape; and then set the measuring cylinder (see Figure 1, which shall meet the requirements of 8.3.3) and the funnel (see Figure 1, which shall meet the requirements of 8.3.4) in place; and keep the device under pressure for 1h.

8.4.4 At the end of the test, raise or drop the measuring cylinder to balance the water level in the measuring cylinder tube and the water tank; and measure the volume of the collected gas by reading the scale on the measuring cylinder tube.

8.4.5 Calibrate the measured volume in accordance with the methods specified in Clauses 4 and 5, and include the gas type and standard temperature and pressure conditions into the calibration calculation.

This is an excerpt of the PDF (Some pages are marked off intentionally)

Full-copy PDF can be purchased from 1 of 2 websites:

1. <https://www.ChineseStandard.us>

- SEARCH the standard ID, such as GB 4943.1-2022.
- Select your country (currency), for example: USA (USD); Germany (Euro).
- Full-copy of PDF (text-editable, true-PDF) can be downloaded in 9 seconds.
- Tax invoice can be downloaded in 9 seconds.
- Receiving emails in 9 seconds (with download links).

2. <https://www.ChineseStandard.net>

- SEARCH the standard ID, such as GB 4943.1-2022.
- Add to cart. Only accept USD (other currencies - <https://www.ChineseStandard.us>).
- Full-copy of PDF (text-editable, true-PDF) can be downloaded in 9 seconds.
- Receiving emails in 9 seconds (with PDFs attached, invoice and download links).

Translated by: Field Test Asia Pte. Ltd. (Incorporated & taxed in Singapore. Tax ID: 201302277C)

About Us (Goodwill, Policies, Fair Trading...): <https://www.chinesestandard.net/AboutUs.aspx>

Contact: Wayne Zheng, Sales@ChineseStandard.net

Linkin: <https://www.linkedin.com/in/waynezhengwenrui/>

----- The End -----