

Translated English of Chinese Standard: GB/T41589-2022

www.ChineseStandard.net → Buy True-PDF → Auto-delivery.

Sales@ChineseStandard.net

GB

NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA

ICS 29.120.50

CCS K 31

GB/T 41589-2022

**In-cable control and protection device for mode 2 charging
of electric road vehicles (IC-CPD)**

电动汽车模式 2 充电的缆上控制与保护装置 (IC-CPD)

(IEC 62752:2018, MOD)

Issued on: July 11, 2022

Implemented on: February 01, 2023

Issued by: State Administration for Market Regulation;

Standardization Administration of the PRC.

Table of Contents

Foreword.....	9
Introduction.....	13
1 Scope.....	14
2 Normative references	15
3 Terms and definitions.....	19
3.1 Terms and definitions relating to plugs and socket-outlets	20
3.2 Terms and definitions relating to terminals.....	21
3.3 Terms and definitions relating to residual current functions.....	23
3.3.1 Terms and definitions relating to currents flowing from live parts to earth	23
3.3.2 Terms and definitions relating to the energization of the residual current function.....	24
3.3.3 Terms and definitions relating to the operation and to the functions of the IC-CPD	25
3.3.4 Terms and definitions relating to values and ranges of energizing quantities	27
3.3.5 Terms and definitions relating to values and ranges of influencing quantities.....	30
3.3.6 Terms and definitions relating to conditions of operation.....	30
3.3.7 Terms and definitions relating to control functions between electric vehicle and IC-CPD	31
3.4 Terms and definitions relating to tests	32
3.5 Terms and definitions relating to construction.....	32
4 Classification.....	33
4.1 According to the supply	33
4.2 According to the construction	33
4.2.1 General	33
4.2.2 IC-CPD including the function box separated from the plug and connector	33
4.2.3 IC-CPD with the function box integrated together with the plug	33
4.2.4 Modular IC-CPD.....	33
4.3 According to the method of connecting the cable(s).....	33
4.3.1 General	33
4.3.2 Non-rewirable IC-CPDs.....	34
4.3.3 IC-CPDs wired by the manufacturer.....	34
4.3.4 Pluggable IC-CPD.....	34
4.4 Classification according to the protective conductor path	34
4.4.1 General	34
4.4.2 IC-CPDs with switched protective conductor.....	34
4.4.3 IC-CPDs with non-switched protective conductor.....	34
4.5 Classification according to behaviour in case of open protective conductor.....	34
4.5.1 General	34
4.5.2 IC-CPD with verification of the availability of the upstream protective conductor	34

.....	35
4.5.3 IC-CPD without verification of the availability of the upstream protective conductor	35
4.6 Classification according to the usage.....	35
5 Characteristics of IC-CPDs.....	35
5.1 Requirements of characteristics	35
5.2 Rated quantities and other characteristics	36
5.2.1 Rated voltages (U_n)	36
5.2.2 Rated current (I_n).....	36
5.2.3 Rated residual operating current ($I_{\Delta n}$)	36
5.2.4 Rated residual non-operating current ($I_{\Delta no}$).....	37
5.2.5 Rated frequency	37
5.2.6 Rated making and breaking capacity (I_m)	37
5.2.7 Rated residual making and breaking capacity ($I_{\Delta m}$)	37
5.2.8 Operating characteristics in case of residual currents comprising a d.c. component	37
5.2.9 Insulation coordination including creepage distances and clearances.....	37
5.2.10 Coordination with short-circuit protection devices (SCPDs).....	37
5.3 Standard and preferred values.....	38
5.3.1 Preferred values of rated operational voltage (U_c)	38
5.3.2 Preferred values of rated current (I_n).....	38
5.3.3 Standard values of rated residual operating current ($I_{\Delta n}$)	38
5.3.4 Standard value of rated residual non-operating current ($I_{\Delta no}$)	38
5.3.5 Standard minimum value of the non-operating overcurrent through the IC-CPD	39
5.3.6 Preferred values of rated frequency	39
5.3.7 Minimum value of the rated making and breaking capacity (I_m)	39
5.3.8 Minimum value of the rated residual making and breaking capacity ($I_{\Delta m}$).....	39
5.3.9 Standard value of the rated conditional short-circuit current (I_{nc}).....	39
5.3.10 Standard value of the rated conditional residual short-circuit current ($I_{\Delta c}$).....	39
5.3.11 Limit values of break time.....	39
6 Marking and other product information.....	40
6.1 Data to be marked on the IC-CPD	40
6.2 Information to be provided to the end-user.....	42
7 Standard conditions for operation in service and for installation	43
7.1 Standard conditions.....	43
7.2 Conditions for installations	44
8 Requirements for construction and operation.....	44
8.1 Mechanical design	44
8.2 Pluggable electrical connections of pluggable IC-CPDs according to 4.3.4	45
8.2.1 General.....	45
8.2.2 Degree of protection of pluggable electrical connection against solid foreign objects	

and water for pluggable IC-CPD.....	46
8.2.3 Breaking capacity of pluggable electrical connection for pluggable IC-CPD	46
8.2.4 Additional requirements	47
8.3 Construction.....	48
8.3.1 General.....	48
8.3.2 Terminations of IC-CPDs.....	48
8.3.3 Enclosure of IC-CPDs according to 4.3.3	49
8.3.4 Terminal screws or nuts of IC-CPDs according to 4.3.3	49
8.3.5 Strain on the conductors of IC-CPDs according to 4.3.3	49
8.3.6 Additional requirements for IC-CPDs according to 4.3.3	49
8.3.7 Insulating parts which keep the live parts in position	50
8.3.8 Screws for IC-CPD according to 4.3.3.....	50
8.3.9 Means for suspension from a wall or other mounting surfaces.....	50
8.3.10 Plug as an integral part of plug-in equipment	50
8.3.11 Flexible cables and cords and their connection.....	51
8.4 Electrical performance	52
8.4.1 Protective conductor path.....	52
8.4.2 Contact mechanism	52
8.4.3 Clearances and creepage distances (see Annex C).....	53
8.5 Protection against electric shock.....	55
8.5.1 General.....	55
8.5.2 Requirements relating to plugs, whether incorporated or not in integral items.....	56
8.5.3 Degree of protection of the function box	56
8.5.4 Requirements relating to vehicle connectors.....	56
8.6 Dielectric properties.....	56
8.7 Temperature rise.....	57
8.8 Operating characteristics.....	57
8.8.1 General.....	57
8.8.2 Safe connection operating characteristic.....	57
8.8.3 Operating characteristics with a.c. residual currents and residual currents having a d.c. component	58
8.8.4 Operating characteristics with smooth d.c. residual current.....	58
8.8.5 Behaviour of the IC-CPD after a residual current operation.....	58
8.9 Mechanical and electrical endurance	58
8.10 Performance at short-circuit currents.....	58
8.11 Resistance to mechanical shock and impact	59
8.12 Resistance to heat.....	59
8.13 Resistance to abnormal heat and to fire	59
8.14 Performance of the test function.....	59
8.15 Behaviour in case of loss of the supply voltage.....	60
8.16 Resistance of IC-CPDs against unwanted tripping due to surge currents to earth resulting from impulse voltages.....	60

8.17 Control pilot function controller	60
8.18 Reliability	60
8.19 Resistance to tracking	61
8.20 Electromagnetic compatibility (EMC).....	61
8.21 Behaviour of the IC-CPD at low ambient air temperature.....	61
8.22 Operation with supply failure and hazardous live protective conductor conditions	61
8.23 Verification of a standing current in the protective conductor in normal service	61
8.24 Behaviour at specific environmental conditions.....	61
8.25 Resistance to vibration and shock.....	62
9 Tests	62
9.1 General.....	62
9.1.1 Opening and closing of contacts	62
9.1.2 Type tests.....	62
9.1.3 Test sequences.....	63
9.1.4 Routine tests.....	64
9.2 Test conditions	64
9.3 Test of indelibility of marking	64
9.4 Protection against electric shock.....	65
9.5 Test of dielectric properties.....	66
9.5.1 Resistance to humidity	66
9.5.2 Insulation resistance of the main circuit.....	66
9.5.3 Dielectric strength of the main circuit.....	67
9.5.4 Secondary circuit of detection transformers.....	68
9.5.5 Verification of impulse withstand voltages (across clearances and across solid insulation) and of leakage current across open contacts	68
9.6 Temperature-rise test.....	72
9.6.1 Test conditions.....	72
9.6.2 Test procedure	72
9.6.3 Measurement of the temperature rise of different parts	72
9.6.4 Temperature rise of a part.....	72
9.7 Verification of the operating characteristic	73
9.7.1 General.....	73
9.7.2 Test circuit.....	73
9.7.3 Residual sinusoidal alternating currents tests.....	73
9.7.4 Verification of the correct operation with residual currents having a d.c. component	76
9.7.5 Verification of behaviour in case of composite residual current	77
9.7.6 Verification of the correct operation in case of smooth d.c. residual current	79
9.7.7 Miswiring and supply failure tests	79
9.7.8 Verification of protective conductor contact behaviour	82
9.7.9 Verification that the protective conductor is connected to the electric vehicle	82

9.7.10 Verification of standing current in the protective conductor in normal service....	83
9.8 Verification of mechanical and electrical endurance	83
9.8.1 Endurance of plug and vehicle connector part	83
9.8.2 Endurance test of the residual current function of the IC-CPD.....	83
9.9 Verification of the behaviour of the IC-CPD under overcurrent conditions	86
9.9.1 List of the overcurrent tests.....	86
9.9.2 Short-circuit tests	86
9.9.3 Verification of the making and breaking capacity of the plug of the IC-CPD	94
9.10 Verification of resistance to mechanical shock and impact	95
9.10.1 General.....	95
9.10.2 Drop test.....	95
9.10.3 Test for screwed glands of IC-CPDs	96
9.10.4 Mechanical strength test on IC-CPDs provided with cords	96
9.11 Test of resistance to heat	97
9.11.1 General	97
9.11.2 Temperature test in heating cabinet.....	97
9.11.3 Ball pressure test for insulating material necessary to retain in position current-carrying parts.....	97
9.11.4 Ball pressure test for insulating material not necessary to retain in position current-carrying parts.....	98
9.12 Resistance of insulating material to abnormal heat and to fire	98
9.13 Verification of the self test	99
9.14 Verification of the behaviour of IC-CPDs in case of loss of the supply voltage....	100
9.14.1 Verification of correct operation at the minimum operating voltage (U_x)	100
9.14.2 Verification of the automatic opening in case of loss of the supply voltage	100
9.14.3 Verification of the reclosing function of IC-CPD.....	101
9.15 Verification of the limiting values of the non-operating current under overcurrent conditions.....	101
9.16 Verification of resistance of IC-CPD against unwanted tripping due to surge currents to earth resulting from impulse voltages.....	101
9.17 Verification of reliability	102
9.17.1 Climatic test	102
9.17.2 Test at a temperature of 50 °C	104
9.18 Verification of resistance to ageing	105
9.19 Resistance to tracking	106
9.20 Test on pins provided with insulating sleeves.....	106
9.21 Test of mechanical strength of non-solid pins of plugs.....	107
9.22 Verification of the effects of strain on the conductors	107
9.23 Checking of the torque exerted by IC-CPDs on fixed socket-outlets	107
9.24 Tests of the cord anchorage.....	107
9.25 Flexing test of non-rewirable IC-CPDs	108

9.26	Verification of the electromagnetic compatibility (EMC)	109
9.27	Tests replacing verifications of creepage distances and clearances	110
9.27.1	General	110
9.27.2	Abnormal conditions	110
9.27.3	Temperature rise resulting from fault conditions	110
9.28	Verifications for single electronic components used in IC-CPDs	112
9.28.1	General	112
9.28.2	Capacitors	112
9.28.3	Resistors and inductors	112
9.29	Chemical loads	115
9.30	Heat test under solar radiation	115
9.31	Resistance to ultra-violet (UV) radiation	115
9.32	Damp and salt mist test for marine and coastal environments	116
9.32.1	Test for internal metallic parts	116
9.32.2	Test for external metallic parts only	116
9.32.3	Test criteria	116
9.33	Hot damp test for tropical environments	117
9.34	Vehicle drive-over	117
9.34.1	General	117
9.34.2	Test at crushing force 5000 N	117
9.34.3	Test at crushing force 11000 N	117
9.34.4	Performance after the tests	117
9.35	Low storage temperature test	118
9.36	Vibration and shock test	118
Annex A	(Normative) Test sequences and number of samples to be submitted for verification of conformity to this document	144
A.1	Verification of conformity	144
A.2	Test sequences	144
A.3	Number of samples to be submitted for full test procedure	146
A.4	Number of samples to be submitted for simplified test procedures in case of submitting simultaneously a range of IC-CPDs of the same fundamental design	148
Annex B	(Normative) Routine tests	151
Annex C	(Normative) Determination of clearances and creepage distances	152
C.1	Overview	152
C.2	Orientation and location of a creepage distance	152
C.3	Creepage distances where more than one material is used	152
C.4	Creepage distances split by a floating conductive part	152
C.5	Measurement of creepage distances and clearances	152
Annex D	(Informative) Switched-protective conductor (SPE) application	158

D.1 Explanation of switched-protective conductor (SPE) function and application	158
D.2 Examples of incorrect supply wiring	159
Annex E (Informative) Example of IC-CPD for mode 2 charging.....	161
Annex F (Informative) Types of IC-CPD according to construction and assembly ..	162
Annex G (Informative) Methods for determination of short-circuit power factor	163
G.1 Overview.....	163
G.2 Method I - Determination from d.c. components.....	163
G.3 Method II - Determination with pilot generator.....	164
Bibliography	165

Foreword

This document is drafted in accordance with GB/T 1.1-2020 "Directives for standardization - Part 1: Rules for the structure and drafting of standardizing documents".

This document modifies and adopts IEC 62752:2018 "In-cable control and protection device for mode 2 charging of electric road vehicles (IC-CPD)".

Compared with IEC 62752:2018, this document has made the following structural adjustments:

- 4.1 corresponds to 4.1.2 in IEC 62752:2018. Delete 4.1.1, 4.1.3, and 4.1.4;
- 4.6 corresponds to 4.6.1 in IEC 62752:2018. Delete 4.6.2 and 4.6.3.

The technical differences between this document and IEC 62752:2018 and their reasons are as follows:

- Use normatively-referenced GB/T 2099.1-2021 to replace IEC 60884-1:2013. The degree of consistency between the two documents is MOD, to adapt to the technical conditions of China and increase operability (see Clause 1, Table 4, 8.1, 8.3.1, 8.4.3, 8.5.2, 9.2, 9.9.3, 9.20, 9.21, 9.23, 9.34.1, A.1);
- Use normatively-referenced GB/T 1043.1 to replace ISO 179-1, to adapt to the technical conditions of China and increase operability (see 9.31);
- Use normatively-referenced GB/T 2423.1 to replace IEC 60068-2-1, to adapt to the technical conditions of China and increase operability (see 9.35);
- Use normatively-referenced GB/T 2423.4 to replace IEC 60068-2-30, to adapt to the technical conditions of China and increase operability (see 9.17.1.1, 9.17.1.4, 9.32.1, 9.32.2);
- Use normatively-referenced GB/T 2423.5 to replace IEC 60068-2-27, to adapt to the technical conditions of China and increase operability (see 9.36);
- Use normatively-referenced GB/T 2423.7 to replace IEC 60068-2-31, to adapt to the technical conditions of China and increase operability (see 9.10.2);
- Use normatively-referenced GB/T 2423.17 to replace IEC 60068-2-11, to adapt to the technical conditions of China and increase operability (see 9.32.1 and 9.32.2);
- Use normatively-referenced GB/T 2423.24 to replace IEC 60068-2-5, to adapt to the technical conditions of China and increase operability (see 9.30);
- Use normatively-referenced GB/T 2423.56 to replace IEC 60068-2-64, to adapt to

In-cable control and protection device for mode 2 charging of electric road vehicles (IC-CPD)

1 Scope

This document applies to in-cable control and protection devices for mode 2 charging of electric road vehicles, hereafter referred to as IC-CPD including control and safety functions.

This document applies to portable devices performing simultaneously the functions of detection of the residual current, of comparison of the value of this current with the residual operating value and of opening of the protected circuit when the residual current exceeds this value.

The IC-CPD according to this document

- has a control pilot function controller in accordance with GB/T 18487.1-2015, Annex A;
- checks supply conditions and prevents charging in case of supply faults under specified conditions;
- may have a switched protective conductor.

These IC-CPDs are intended for use in TN-, and TT-systems. The use in IT systems may be limited.

Residual currents with frequencies different from the rated frequency, d.c. residual currents and specific environmental situation are considered.

This document is applicable to IC-CPDs performing the safety and control functions as required in GB/T 18487.1 for mode 2 charging of electric vehicles.

This document is applicable to IC-CPDs for single-phase circuits not exceeding 250 V, their maximum rated current not exceeding 16 A.

This document is applicable to IC-CPDs to be used in a.c. circuits only, with preferred values of rated frequency 50 Hz, 60 Hz or 50/60 Hz. IC-CPDs according to this document are not intended to be used to supply electric energy towards the connected grid.

This document is applicable to IC-CPDs having a rated residual operating current not exceeding 30 mA and are intended to provide additional protection for the circuit downstream of the IC-CPD in situations where it cannot be guaranteed that the

installation is equipped with an RCD with $I_{\Delta n} \leq 30$ mA.

The IC-CPD consists of:

- a plug for connection to a socket-outlet in the fixed installation;
- one or more subassemblies containing the control and protection features;
- a cable between the plug and the subassemblies (optional);
- a cable between the subassemblies and the vehicle connector (optional);
- a vehicle connector for connection to the electric vehicle.

For plugs for household and similar use GB/T 2099.1-2021 apply. Types, basic parameters and dimensions are in accordance with GB/T 1002.

Plugs, connectors and cables which are part of the IC-CPD are not tested according to this document. These parts are tested separately according to their specific product standard.

The switching contacts of the IC-CPD are not required to provide isolation, as isolation can be ensured by disconnecting the plug.

The IC-CPD may have a non-replaceable integral fuse in the phase(s) and/or neutral current path.

The IC-CPD is not considered to be a protective device for use in fixed installations.

2 Normative references

The contents of the following documents, through normative references in this text, constitute indispensable provisions of this document. Among them, for dated references, only the edition corresponding to that date applies to this document. For undated references, the latest edition (including all amendments) applies to this document.

GB/T 1002 Single phase plugs and socket-outlets for household and similar purposes
- Types, basic parameters and dimensions

GB/T 1043 (all parts) Plastics - Determination of Charpy impact properties [ISO 179 (all parts)]

Note: GB/T 1043.1-2008 Plastics - Determination of Charpy impact properties - Part 1: Non-instrumented impact test (ISO 179-1:2000, IDT);

GB/T 1043.2-2008 Plastics - Determination of Charpy impact properties - Part 2: Instrumented impact test (ISO 179-2:1997, IDT).

This is an excerpt of the PDF (Some pages are marked off intentionally)

Full-copy PDF can be purchased from 1 of 2 websites:

1. <https://www.ChineseStandard.us>

- SEARCH the standard ID, such as GB 4943.1-2022.
- Select your country (currency), for example: USA (USD); Germany (Euro).
- Full-copy of PDF (text-editable, true-PDF) can be downloaded in 9 seconds.
- Tax invoice can be downloaded in 9 seconds.
- Receiving emails in 9 seconds (with download links).

2. <https://www.ChineseStandard.net>

- SEARCH the standard ID, such as GB 4943.1-2022.
- Add to cart. Only accept USD (other currencies - <https://www.ChineseStandard.us>).
- Full-copy of PDF (text-editable, true-PDF) can be downloaded in 9 seconds.
- Receiving emails in 9 seconds (with PDFs attached, invoice and download links).

Translated by: Field Test Asia Pte. Ltd. (Incorporated & taxed in Singapore. Tax ID: 201302277C)

Accountable person and shareholder: Wayne Zheng

About Us (Goodwill, Policies, Fair Trading...): <https://www.chinesestandard.net/AboutUs.aspx>

Contact: Wayne Zheng, Sales@ChineseStandard.net

Linkin: <https://www.linkedin.com/in/waynezhengwenrui/>

----- The End -----