

Translated English of Chinese Standard: GB/T12535-2021

www.ChineseStandard.net → Buy True-PDF → Auto-delivery.

Sales@ChineseStandard.net

GB

NATIONAL STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA

ICS 43.020
CCS T 04

GB/T 12535-2021

Replacing GB/T 12535-2007

Test method of starting performance for motor vehicle

汽车起动性能试验方法

Issued on: October 11, 2021

Implemented on: May 01, 2022

**Issued by: State Administration for Market Regulation;
Standardization Administration of the PRC.**

Table of Contents

Foreword.....	3
1 Scope.....	6
2 Normative references.....	6
3 Terms and definitions	6
4 Measurement parameters.....	7
5 Test conditions	7
6 Test methods.....	9
7 Test records	12
Appendix A (Informative) Test records	13

Test method of starting performance for motor vehicle

1 Scope

This document specifies the measurement parameters, test conditions, test methods, and test records of starting performance for motor vehicle.

This document applies to category M and N motor vehicles.

2 Normative references

The contents of the following documents, through normative references in this text, constitute indispensable provisions of this document. Among them, for dated references, only the edition corresponding to that date applies to this document. For undated references, the latest edition (including all amendments) applies to this document.

GB/T 12428 Laden mass calculating method for buses

GB/T 12534-1990 Motor vehicles - General rules of road test method

GB/T 15089 Classification of power-driven vehicles and trailers

GB/T 19596 Terminology of electric vehicles

3 Terms and definitions

The terms and definitions defined in GB/T 15089 and GB/T 19596 and the following ones apply to this document.

3.1

Cranking time

The time from when the starter is turned on until the engine speed reaches the idling speed specified by the manufacturer under the condition that the motor vehicle's engine is successfully started.

3.2

Starting performance

and thermal insulation devices (engine insulation cover, radiator insulation device and battery incubator, etc.). However, the starting accessories shall be the standard configuration of the vehicle manufacturer. It shall not use configurations other than those specified by the manufacturer. During the test, the auxiliary starting devices and the thermal insulation devices shall be operated according to the instruction manual.

5.1.4 The battery, starting cable, and earthed cable specified by the vehicle manufacturer shall be used. All circuits shall be connected reliably. The battery shall work well. Before the vehicle starts to stand still, the electric quantity and voltage of energy storage batteries such as the battery or power battery of the vehicle shall be within the range specified by the vehicle manufacturer.

5.1.5 The parking brake of the test vehicle shall be released.

5.2 Test site

5.2.1 When the test is carried out outdoors, the road on which the test vehicle is parked shall be level, solid, smooth and dry.

5.2.2 When the test is carried out indoors, the environmental test room shall have facilities such as chassis dynamometer, low-temperature environment chamber, and plateau environment chamber that meet the test requirements.

5.3 Test mass and load distribution

5.3.1 For category M_1 vehicles, and category N_1 vehicles with a maximum design total mass less than 2000 kg, it shall be in accordance with the following requirements:

- When 50% of the maximum allowable laden mass of the vehicle is less than or equal to 180 kg, the test mass is the curb mass of the complete vehicle plus 180 kg (including the mass of measuring personnel and instruments);
- When 50% of the maximum allowable laden mass of the vehicle is greater than 180 kg, the test mass of the vehicle is the curb mass of the complete vehicle plus 50% of the maximum allowable laden mass (including the mass of measuring personnel and instruments). The load distribution shall be as uniform as possible.

5.3.2 For category M_2 and M_3 vehicles, and category N vehicles with a maximum design total mass not less than 2000 kg, it shall be in accordance with the following requirements:

- Except for special provisions, 65% of the laden mass is applicable to category M_2 and M_3 buses; other motor vehicles shall be fully loaded;

6.2.4.1 If the power source for cold starting is engine, carry out the test in accordance with the provisions of 6.2.2.

6.2.4.2 If the power source for cold starting is power battery, carry out the test in accordance with the provisions of 6.2.3.

6.2.5 Cold starting test of fuel cell electric vehicle

Start the vehicle in accordance with the vehicle manufacturer's recommended starting procedures. Record the time from when the vehicle is powered on to when the "READY" or "OK" signal device lights up.

6.3 Preheating test

6.3.1 Preheating test of internal combustion engine vehicle

After the engine is started, for motor vehicles with manual transmission, the clutch can continue to be disengaged; the gear lever remains in neutral. For motor vehicles with automatic transmission, the transmission remains in P position. Idle in place for 5 min.

6.3.2 Preheating test of pure electric vehicle, extended-range electric vehicle, and fuel cell electric vehicle

Pure electric vehicles, extended-range electric vehicles, and fuel cell electric vehicles can directly enter the starting test without preheating test. If preheating is required, the preheating time shall not exceed 5 min.

6.3.3 Preheating test of hybrid electric vehicle except extended-range electric vehicle

6.3.3.1 If the power source for cold starting is engine, carry out the test in accordance with the provisions of 6.3.1.

6.3.3.2 If the power source for cold starting is power battery, carry out the test in accordance with the provisions of 6.3.2.

6.4 Starting test

6.4.1 After starting and preheating tests, put the vehicle in reverse gear and start in reverse; travel no less than 3 m.

6.4.2 After parking, the motor vehicle starts in the lowest forward gear.

6.4.3 If any one of 6.4.1 and 6.4.2 fails, the item can be repeated once. If it still fails to start, it is determined that the starting test has failed.

This is an excerpt of the PDF (Some pages are marked off intentionally)

Full-copy PDF can be purchased from 1 of 2 websites:

1. <https://www.ChineseStandard.us>

- SEARCH the standard ID, such as GB 4943.1-2022.
- Select your country (currency), for example: USA (USD); Germany (Euro).
- Full-copy of PDF (text-editable, true-PDF) can be downloaded in 9 seconds.
- Tax invoice can be downloaded in 9 seconds.
- Receiving emails in 9 seconds (with download links).

2. <https://www.ChineseStandard.net>

- SEARCH the standard ID, such as GB 4943.1-2022.
- Add to cart. Only accept USD (other currencies - <https://www.ChineseStandard.us>).
- Full-copy of PDF (text-editable, true-PDF) can be downloaded in 9 seconds.
- Receiving emails in 9 seconds (with PDFs attached, invoice and download links).

Translated by: Field Test Asia Pte. Ltd. (Incorporated & taxed in Singapore. Tax ID: 201302277C)

About Us (Goodwill, Policies, Fair Trading...): <https://www.chinesestandard.net/AboutUs.aspx>

Contact: Wayne Zheng, Sales@ChineseStandard.net

Linkin: <https://www.linkedin.com/in/waynezhengwenrui/>

----- The End -----